

View Online at <https://aerobasegroup.com/nsn/5950-01-480-7915>

Reliability Indicator:

Not established

Impedance Rating In Ohms:

4000.0 single component single primary

Frequency Rating:

75.0 kilohertz single component and 1.0 megahertz single component

Primary To Secondary Turn Ratio:

1 to 1 to .707 single component

Body Length:

0.625 inches

Body Width:

0.625 inches

Body Height:

0.275 inches

Maximum Operating Temp:

130.0 degrees celsius

End Application:

Hamilton stan, wsd: engine, aircraft f100-pw-229 (f15e, f16c/d)

Inclosure Type:

Fully enclosed

Mounting Method:

Terminal single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Dc Resistance Rating In Ohms:

3.000 single component single secondary

Test Data Document:

81349-mil-prf-21038 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

8 printed circuit

Specification Data:

81349-mil-prf-21038/27-11 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0

Mil-std (military Standard):

Mil-prf-21038 spec.