

View Online at <https://aerobasegroup.com/nsn/5950-01-480-7915>

**Reliability Indicator:**

Not established

**Impedance Rating In Ohms:**

4000.0 single component single primary

**Frequency Rating:**

75.0 kilohertz single component and 1.0 megahertz single component

**Primary To Secondary Turn Ratio:**

1 to 1 to .707 single component

**Body Length:**

0.625 inches

**Body Width:**

0.625 inches

**Body Height:**

0.275 inches

**Maximum Operating Temp:**

130.0 degrees celsius

**End Application:**

Hamilton stan, wsd: engine, aircraft f100-pw-229 (f15e, f16c/d)

**Inclosure Type:**

Fully enclosed

**Mounting Method:**

Terminal single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Dc Resistance Rating In Ohms:**

3.000 single component single secondary

**Test Data Document:**

81349-mil-prf-21038 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

8 printed circuit

**Specification Data:**

81349-mil-prf-21038/27-11 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0

**Mil-std (military Standard):**

Mil-prf-21038 spec.