

View Online at <https://aerobasegroup.com/nsn/5950-01-481-6864>

Reliability Indicator:

Not established

Overall Length:

0.110 inches

Overall Height:

0.070 inches

Overall Width:

0.105 inches

Inductance Rating:

10.00 microhenries single component single winding

End Application:

Nsn: 1240-01-460-6103 integrated sight as; wsd: missile, tow (ground-tow i & ii)

Inclosure Type:

Fully enclosed

Rating Method:

Electrical single component single winding

Winding Operating Current:

87.0 milliamperes ac single component single winding

Dc Resistance Rating In Ohms:

3.300 single component single primary

Quality Factor:

36 single component single winding

Special Features:

Operating temperature range -55 deg. C to +125 degrees c

Test Data Document:

81349-mil-prf-83446 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 bonding pad

Specification Data:

81349-mil-prf-83446/08-86b government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0

Mil-std (military Standard):

Mil-prf-83446 spec.