

View Online at <https://aerobasegroup.com/nsn/5950-01-481-6864>

**Reliability Indicator:**

Not established

**Overall Length:**

0.110 inches

**Overall Height:**

0.070 inches

**Overall Width:**

0.105 inches

**Inductance Rating:**

10.00 microhenries single component single winding

**End Application:**

Nsn: 1240-01-460-6103 integrated sight as; wsd: missile, tow (ground-tow i & ii)

**Inclosure Type:**

Fully enclosed

**Rating Method:**

Electrical single component single winding

**Winding Operating Current:**

87.0 milliamperes ac single component single winding

**Dc Resistance Rating In Ohms:**

3.300 single component single primary

**Quality Factor:**

36 single component single winding

**Special Features:**

Operating temperature range -55 deg. C to +125 degrees c

**Test Data Document:**

81349-mil-prf-83446 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 bonding pad

**Specification Data:**

81349-mil-prf-83446/08-86b government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A058b0

**Mil-std (military Standard):**

Mil-prf-83446 spec.