## NSN 5950-01-482-0824

Radio Frequency Coil - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-482-0824

| view Offilite at https://aerobasegroup.com/histi/03300-01-402-0024   |
|--|
| Reliability Indicator:   |
| Not established  |
| Inductance Rating:   |
| 12.00 microhenries single component single winding   |
| Coil Form Type:  |
| Solid single component   |
| Core Construction:   |
| Solid single component   |
| Body Length:   |
| 0.155 inches   |
| Body Width:  |
| 0.125 inches   |
| Body Height:   |
| 0.130 inches   |
| End Application:   |
| F/a-18e/f  |
| Inclosure Type:  |
| Fully enclosed   |
| Mounting Method:   |
| Terminal single group  |
| Rating Method:   |
| Electrical single component single winding   |
| Winding Operating Current:   |
| 180.0 milliamperes ac single component single winding  |
| Dc Resistance Rating In Ohms:  |
| 1.500 single component single winding  |
| Criticality Code Justification:  |
| Agav   |
| Special Features:  |
| Final finish is tin-lead   |
| Test Data Document:  |
| 81349-mil-prf-83446 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain            |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                              |
| Terminal Type And Quantity:  |
| 1 printed circuit  |
| Specification Data:  |
| 81349-mil-prf-83446/11 government specification  |
| Shelf Life:  |
| N/a  |
| Unit Of Measure:   |
|  |
| Demilitarization:  |

No

## NSN 5950-01-482-0824

Radio Frequency Coil - Page 2 of 2



Fiig:

A058b0

Mil-std (military Standard):

Mil-prf-83446 spec.