## NSN 5950-01-484-1771

Power Transformer - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-484-1771 **Reliability Indicator:** Not established **Overall Length:** 13.500 inches Center To Center Distance Between Mounting Facilities Parallel To Length: 8.630 inches single mounting facility single center group Center To Center Distance Between Mounting Facilities Parallel To Width: 8.000 inches single mounting facility single center group **Overall Height:** 10.100 inches **Overall Width:** 9.000 inches **Mounting Slot Width:** 0.280 inches single group Frequency Rating: 47.0 hertz single component and 65.0 hertz single component Input-output Phase Relationship: Single phase to single phase single component **Maximum Transformer Power Rating:** 10.0 kilovolt-ampere single component **Maximum Operating Temp:** 60.0 degrees celsius **End Application:** Reentry system test set **Inclosure Type:** Open **Mounting Facility Quantity:** 4 single group **Mounting Method:** Slot single group **Winding Function And Quantity:** 2 primary single component and 2 secondary single component **Winding Operating Voltage:** 104.00 ac volts single component all secondary and 110.00 ac volts single component all secondary and 120.00 ac volts single component all secondary **Special Features:** Name on drawing is transformer, isolation **Terminal Type And Quantity:** 16 threaded stud Shelf Life:

N/a

**Unit Of Measure:** 

## NSN 5950-01-484-1771

Power Transformer - Page 2 of 2



Demilitarization:

No

Fiig:

A058b0