

View Online at <https://aerobasegroup.com/nsn/5950-01-490-1931>

Reliability Indicator:

Not established

Overall Length:

152.0 millimeters

Center To Center Distance Between Mounting Facilities Parallel To Length:

51.0 millimeters single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

53.0 millimeters single mounting facility single center group

Overall Height:

127.0 millimeters

Overall Width:

76.0 millimeters

Inductance Type:

Fixed

Inductance Rating:

3.00 microhenries single component single winding

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

End Application:

Panel; wsd: nimitz class cvn

Winding Quantity:

3 single component

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Rating Method:

Electrical single component single winding

Winding Operating Current:

8.0 amperes ac single component single secondary and 12.0 amperes ac single component single secondary

Special Features:

Ambient temp. 0 degrees c to +60 degrees c; maximum voltage: 600 vac; iron core, 3% or 5% impedance based on fundamental current ratings

Terminal Type And Quantity:

1 terminal block w/screws

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A058b0