

View Online at <https://aerobasegroup.com/nsn/5950-01-490-3465>

Reliability Indicator:

Not established

Overall Length:

4.990 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.430 inches single mounting facility single center group and 4.470 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.680 inches single mounting facility single center group and 2.720 inches single mounting facility single center group

Overall Height:

1.940 inches

Frequency Rating:

380.0 hertz single component and 420.0 hertz single component

Input-output Phase Relationship:

Three phase to three phase single component

Transformer Winding Connection Type:

Delta-delta or delta-wye

Body Width:

3.240 inches

Maximum Operating Temp:

130.0 degrees celsius

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Threaded hole single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Thread Size:

0.164 inches single group

Winding Operating Current:

8.34 amperes ac single component single secondary

Winding Operating Voltage:

15.00 ac volts single component single secondary

Test Data Document:

81349-mil-t-27 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Thread Series Designator:

Unc single group

Terminal Type And Quantity:

10 turret

Specification Data:

81349-mil-t-27/349 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0