NSN 5950-01-493-7333

Power Transformer - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5950-01-493-7333 |
|---|
| Reliability Indicator: |
| Not established |
| Overall Length: |
| 8.030 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 5.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 3.500 inches single mounting facility single center group |
| Overall Height: |
| Between 6.500 inches and 6.590 inches |
| Overall Width: |
| 7.800 inches |
| Mounting Hole Diameter: |
| 0.312 inches single group |
| Frequency Rating: |
| 400.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| End Application: |
| Next assembly 13038207; nsn: 1430-01-184-6768, radar set, semitrailer mounted |
| Inclosure Type: |
| Fully enclosed |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 1 primary single component and 4 secondary single component |
| Winding Operating Current: |
| 10.0 amperes dc single component single secondary |
| Winding Operating Voltage: |
| 416.00 ac pounds per hour with retaining chain single component single primary |
| Special Features: |
| Soperating temp. Range: -40 to +85 deg. C; primary dc winding resistance: 0.25 ohms maximum between terminals 1-2 or 1-3 and 0.35 |
| ohms maximum between terminals 2-3; secondary dc winding resistance: 0.08 ohms max, j1 pins 0.23 ohms max |
| Terminal Type And Quantity: |
| 11 screw |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |

Yes - demil/mli

Demilitarization:

NSN 5950-01-493-7333

Power Transformer - Page 2 of 2



Fiig:

A058b0