NSN 5950-01-504-6879

Current Transformer - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5950-01-504-6879

| Reliability Indicator: |
|--|
| Not established |
| Center To Center Distance Between Mounting Facilities Parallel To Length: |
| 2.750 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width: |
| 2.750 inches single mounting facility single center group |
| Mounting Hole Diameter: |
| 0.281 inches single group |
| Frequency Rating: |
| 25.0 hertz single component and 800.0 hertz single component |
| Input-output Phase Relationship: |
| Single phase to single phase single component |
| Body Length: |
| 3.750 inches |
| Body Width: |
| 3.625 inches |
| Body Height: |
| 1.062 inches |
| Inclosure Type: |
| Open |
| Mounting Facility Quantity: |
| 4 single group |
| Mounting Method: |
| Unthreaded hole single group |
| Winding Function And Quantity: |
| 1 secondary single component |
| Winding Operating Current: |
| 200.0 amperes ac single component single primary |
| Special Features: |
| Center hole is 3.5 in. Dia; 2 cadmium plated steel brackets and bolts supplied |
| Terminal Type And Quantity: |
| 2 threaded stud |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A058b0 |