NSN 5950-01-508-9537

Reactor - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-508-9537 **Reliability Indicator:** Not established **Mounting Hole Diameter:** 0.140 inches single group Frequency Rating: 60.0 hertz single component **Overall Diameter:** 2.530 inches **Maximum Operating Temp:** 130.0 degrees celsius **End Application:** C-17a Winding Quantity: 4 single component **Inclosure Type:** Hermetically sealed **Mounting Facility Quantity:** 1 single group **Mounting Method:** Unthreaded hole single group **Rating Method:** Electrical single component single primary **Winding Operating Current:** 22.5 amperes dc single component single primary Dc Resistance Rating In Ohms: 10.000 single component single primary **Special Features:** Requested nameoutput filter chokeassembly **Test Data Document:** 19623-007814 drawing (this is the basic governing drawing, such as a contractor drawing, original equipment manufacturer drawing, etc.; excludes any specification, standard or other document that may be referenced in a basic governing drawing) **Terminal Type And Quantity:** 2 wire hook **Specification Data:** 81349-mil-prf-27 government specification Shelf Life: N/a **Unit Of Measure:**

No

Demilitarization:

Fiig:

A058b0

NSN 5950-01-508-9537

Reactor - Page 2 of 2



Mil-std (military Standard):

Mil-prf-27 spec.