

View Online at <https://aerobasegroup.com/nsn/5950-01-510-3802>

Reliability Indicator:

Not established

Overall Length:

Between 5.480 inches and 5.500 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.360 inches single mounting facility single center group and 4.400 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.610 inches single mounting facility single center group and 3.650 inches single mounting facility single center group

Overall Height:

Between 4.540 inches and 4.560 inches

Overall Width:

Between 4.730 inches and 4.750 inches

Mounting Slot Width:

0.280 inches single group

Frequency Rating:

60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

50.0 degrees celsius

End Application:

Ordalt 20351, 20352, 20353, hd-1157/s, hd-1074/sqs, hd1077/ssq, clr, wtr, elek eqpt; wsd: arleigh burke class ddg

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

6.8 amperes ac single component single secondary

Winding Operating Voltage:

440.00 ac pounds per hour wet single component single primary input

Special Features:

Terminals consist of horizontal tin-plated brass lugs w/6-32 thread

Terminal Type And Quantity:

4 tab w/screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0