

View Online at <https://aerobasegroup.com/nsn/5950-01-510-3802>

**Reliability Indicator:**

Not established

**Overall Length:**

Between 5.480 inches and 5.500 inches

**Center To Center Distance Between Mounting Facilities Parallel To Length:**

4.360 inches single mounting facility single center group and 4.400 inches single mounting facility single center group

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

3.610 inches single mounting facility single center group and 3.650 inches single mounting facility single center group

**Overall Height:**

Between 4.540 inches and 4.560 inches

**Overall Width:**

Between 4.730 inches and 4.750 inches

**Mounting Slot Width:**

0.280 inches single group

**Frequency Rating:**

60.0 hertz single component

**Input-output Phase Relationship:**

Single phase to single phase single component

**Maximum Operating Temp:**

50.0 degrees celsius

**End Application:**

Ordalt 20351, 20352, 20353, hd-1157/s, hd-1074/sqs, hd1077/ssq, clr, wtr, elek eqpt; wsd: arleigh burke class ddg

**Inclosure Type:**

Fully enclosed

**Mounting Facility Quantity:**

4 single group

**Mounting Method:**

Slot single group

**Winding Function And Quantity:**

1 primary single component and 1 secondary single component

**Winding Operating Current:**

6.8 amperes ac single component single secondary

**Winding Operating Voltage:**

440.00 ac pounds per hour wet single component single primary input

**Special Features:**

Terminals consist of horizontal tin-plated brass lugs w/6-32 thread

**Terminal Type And Quantity:**

4 tab w/screw

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A058b0