## NSN 5950-01-519-3948

Transformer Assembly - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5950-01-519-3948

| View Online at https://aerobasegroup.com/nsn/5950-01-519-3948   |
|---|
| Reliability Indicator:  |
| Not established   |
| Center To Center Distance Between Mounting Facilities Parallel To Length:   |
| 1.500 inches single mounting facility single center group and 1.600 inches single mounting facility single center group |
| Center To Center Distance Between Mounting Facilities Parallel To Width:  |
| 0.120 inches single mounting facility single center group and 0.650 inches single mounting facility single center group |
| Frequency Rating:   |
| 10.000 kilohertz single component   |
| Maximum Transformer Power Rating:   |
| 0.2 watts single component  |
| Body Width:   |
| 0.120 inches  |
| Body Height:  |
| 1.200 inches  |
| Maximum Operating Temp:   |
| 65.0 degrees celsius  |
| End Application:  |
| Mmrt  |
| Inclosure Type:   |
| Hermetically sealed   |
| Mounting Facility Quantity:   |
| 2 single group  |
| Mounting Method:  |
| Threaded hole single group  |
| Rating Method:  |
| Electrical single component single primary  |
| Winding Function And Quantity:  |
| 2 primary 1st component and 2 secondary 1st component   |
| Thread Size:  |
| 0.112 inches single group   |
| Special Features:   |
| $2\ floating\ coaxial\ connected\ 5\ and\ 6\ connected\ 7\ and\ 8\ connected$   |
| Thread Series Designator:   |
| Unc single group  |
| Terminal Type And Quantity:   |
| 8 turret  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
| <del></del>   |
| Demilitarization:   |

No

## **NSN 5950-01-519-3948** Transformer Assembly - Page 2 of 2



Fiig:

A058b0