

View Online at <https://aerobasegroup.com/nsn/5950-01-524-0536>

Reliability Indicator:

Not established

Overall Length:

3.880 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

2.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

2.500 inches single mounting facility single center group

Overall Height:

3.630 inches

Overall Width:

3.130 inches

Mounting Slot Width:

3.130 inches single group

Frequency Rating:

50.0 hertz single component and 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

End Application:

Cp-140 aircraft

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Operating Current:

2.2 amperes ac single component single primary input

Winding Operating Voltage:

230.00 ac pounds per hour wet single component single primary input

Special Features:

Between kauto transformer which has one winding that is tapped to achieve specific output voltage; input cord length 5-1/2 feet and output cord is 8 inches ; operating temperature of 105 degrees c

Terminal Type And Quantity:

2 cable w/connector

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A058b0