

View Online at <https://aerobasegroup.com/nsn/5950-01-529-9386>

Reliability Indicator:

Not established

Overall Length:

5.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

3.750 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

3.750 inches single mounting facility single center group

Overall Height:

3.820 inches

Overall Width:

4.500 inches

Mounting Slot Width:

0.203 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

Maximum Operating Temp:

105.0 degrees celsius

End Application:

04s004wt (31px6), dual generator, main switchboard; 04s004bm (31px6), single generator

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Function And Quantity:

1 primary single component and 1 secondary single component

Winding Operating Current:

3.0 amperes ac single component single primary

Winding Operating Voltage:

240.00 ac pounds per hour wet single component single primary or 480.00 ac pounds per hour wet single component single primary

Special Features:

Navy: transformer, control; primary voltages: 240x480, 230x460, 220x440; secondary voltages: 120, 115, 110, va350

Terminal Type And Quantity:

8 screw

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A058b0