

View Online at <https://aerobasegroup.com/nsn/5950-01-562-6727>

Reliability Indicator:

Not established

Overall Length:

5.250 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

4.375 inches single mounting facility single center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

4.125 inches single mounting facility single center group

Overall Height:

4.375 inches

Overall Width:

5.625 inches

Mounting Slot Width:

0.250 inches single group

Frequency Rating:

50.0 hertz single component or 60.0 hertz single component

Input-output Phase Relationship:

Single phase to single phase single component

End Application:

An/gsc-7 (v) 1, isil, next assembly a3298657 used on ka-stars

Inclosure Type:

Open

Mounting Facility Quantity:

4 single group

Mounting Method:

Slot single group

Winding Operating Current:

25.0 amperes ac single component single secondary

Winding Operating Voltage:

24.00 ac pounds per hour wet single component single secondary

Product Name:

Rectified power transformer (powervolt)

Special Features:

Secondary rms rating parallel 12vct at 50a

Terminal Type And Quantity:

8 pin

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0