

View Online at <https://aerobasegroup.com/nsn/5950-01-577-9546>

Reliability Indicator:

Not established

Overall Length:

14.750 inches

Center To Center Distance Between Mounting Facilities Parallel To Length:

8.000 inches single mounting facili type 1st center group

Center To Center Distance Between Mounting Facilities Parallel To Width:

12.000 inches single mounting facili type 2nd center group

Overall Height:

9.000 inches

Overall Width:

13.500 inches

Mounting Hole Diameter:

0.560 inches single group

Mounting Slot Width:

0.312 inches 1st group

Frequency Rating:

60.0 hertz single component

End Application:

Misc electric plant group lsd 0044

Inclosure Type:

Fully enclosed

Mounting Facility Quantity:

2 1st group

Mounting Method:

Unthreaded hole single group

Winding Operating Current:

13.6 amperes ac single component single secondary

Winding Operating Voltage:

220.00 ac volts single component single secondary

Product Name:

3kva resin filled transformer

Special Features:

3 phase, high voltage 120 delta, low voltage 220 delta, knoclouts for 0.75 x 1.0 conduit, ul/cul listed nema 3r outdoor enclosure copper wound; appx. 125 lbs

Terminal Type And Quantity:

10 wire lead

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A058b0