## NSN 5955-00-001-7535

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-001-7535

View Online at https://aerobasegroup.com/nsn/5955-00-001-7535
Overall Length:
Between 0.440 inches and 0.450 inches
Terminal Length:
Between 0.271 inches and 0.359 inches
Diameter:
Between 0.695 inches and 0.715 inches
Overall Diameter:
Between 0.740 inches and 0.760 inches
Terminal Diameter:
Between 0.038 inches and 0.042 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
8.290155 megahertz
Holder Cover Material:
Metal
Distance Between Center Terminal And Outside Terminal Centers:
0.094 inches
Operating Tempurature Range:
-55.0 to 105.0 degrees celsius
Center To Center Distance Between Terminals:
0.188 inches
0.188 inches  Drive Level Rating:
Drive Level Rating:
Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts
Drive Level Rating:  Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent:
Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005 to 0.005
Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005 to 0.005 Second Center To Center Distance Between Terminals:
Drive Level Rating:  Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.005 to 0.005  Second Center To Center Distance Between Terminals: 0.125 inches
Drive Level Rating: Between 8.0 milliwatts and 12.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.005 to 0.005 Second Center To Center Distance Between Terminals: 0.125 inches Equivalent Resistance Value In Ohms:
Drive Level Rating:  Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.005 to 0.005  Second Center To Center Distance Between Terminals: 0.125 inches  Equivalent Resistance Value In Ohms: 20.0
Drive Level Rating:  Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.005 to 0.005  Second Center To Center Distance Between Terminals: 0.125 inches  Equivalent Resistance Value In Ohms: 20.0  Style Designator:
Drive Level Rating:  Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.005 to 0.005  Second Center To Center Distance Between Terminals: 0.125 inches  Equivalent Resistance Value In Ohms: 20.0  Style Designator: Hat type, 5 wire leads
Drive Level Rating:  Between 8.0 milliwatts and 12.0 milliwatts  Frequency Tolerance For Operating Tempurature In Percent: -0.005 to 0.005  Second Center To Center Distance Between Terminals: 0.125 inches  Equivalent Resistance Value In Ohms: 20.0  Style Designator: Hat type, 5 wire leads  Shelf Life:

Demilitarization:

Yes - demil/mli

## **NSN 5955-00-001-7535**Quartz Crystal Unit - Page 2 of 2



Fiig:

A059a0