# NSN 5955-00-009-3113

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-009-3113

# **Overall Length:**

0.530 inches

## **Terminal Length:**

Between 0.500 inches and 0.830 inches

# **Overall Width:**

0.435 inches

#### **Body Width:**

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

**Terminal Diameter:** 

Between 0.016 inches and 0.019 inches

### Mode Of Oscillation:

Third overtone

### **Circuit Resonance:**

Series resonance

### Shunt Capacitance In Picofarads:

3.5

#### Specified Frequency:

32.916666 megahertz

# Holder Cover Material:

Metal

## Operating Tempurature Range:

-40.0 to 90.0 degrees celsius and -55.0 to 105.0 degrees celsius

## **Center To Center Distance Between Terminals:**

0.184 mils and 0.200 centimeters

#### **Drive Level Rating:**

Between 1.6 milliwatts and 2.4 milliwatts

## Frequency Tolerance For Operating Tempurature In Percent:

-0.002/+0.002 and -0.003/+0.003

## **Equivalent Resistance Value In Ohms:**

40.0

# Style Designator:

Oval body, wire leads

# **Test Data Document:**

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# Specification Data:

81349-mil-c-3098/53 government specification

# Shelf Life:

# NSN 5955-00-009-3113

Quartz Crystal Unit - Page 2 of 2

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0

