NSN 5955-00-043-2007



Quartz Crystal Unit - Page 1 of 2
View Online at https://aerobasegroup.com/nsn/5955-00-043-2007
Overall Length:
0.530 inches
Terminal Length:
1.500 inches
Overall Width:
0.435 inches
Overall Thickness:
0.183 inches
Terminal Diameter:
Between 0.016 inches and 0.019 inches
Mode Of Oscillation:
Fifth overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
5.5
Specified Frequency:
85.000 megahertz
Frequency Tolerance At Reference Tempurature In Percent:
-0.001/+0.001
Frequency Stability In Percent:
-0.00025 to 0.00025
Controlled Reference Temp:
85.0 degrees celsius
Operable Tempurature Range:
-55.0/+105.0 degrees celsius
Holder Cover Material:
Glass
Operating Tempurature Range:
+80.0/+90.0 degrees celsius
Center To Center Distance Between Terminals:
0.184 mils and 0.200 inches
Drive Level Rating:
Between 1.6 milliwatts and 2.4 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.001/+0.001
Equivalent Resistance Value In Ohms:
50.0
Style Designator:
Oval body, wire leads
Test Data Document:
81340-mil-c-3008 specification (includes engineering type bulleting

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

NSN 5955-00-043-2007

Quartz Crystal Unit - Page 2 of 2



Specification Data:

81349-mil-c-3098/84 government specification

Shelf Life:

N/a

Unit Of Measure:

Demilitarization:

No

Fiig:

A059a0