NSN 5955-00-057-2746

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-057-2746

Overall Length:
0.755 inches
Terminal Length:
0.238 inches
Overall Width:
0.418 inches
Body Length:
0.515 inches
Body Width:
0.399 inches
Body Thickness:
0.147 inches
Overall Thickness:
0.166 inches
Terminal Diameter:
0.040 inches
Mode Of Oscillation:
Fifth overtone and third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
5.0
Specified Frequency:
99.00027 megahertz
Controlled Reference Temp:
75.0 degrees celsius
Holder Cover Material:
Metal
Metal Operating Tempurature Range:
Operating Tempurature Range:
Operating Tempurature Range: +70.0/+80.0 degrees celsius
Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals:
Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.192 inches
Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.192 inches Drive Level Rating:
Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.192 inches Drive Level Rating: Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts
Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.192 inches Drive Level Rating: Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent:
Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.192 inches Drive Level Rating: Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.003/+0.003
Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.192 inches Drive Level Rating: Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.003/+0.003 Equivalent Resistance Value In Ohms:
Operating Tempurature Range: +70.0/+80.0 degrees celsius Center To Center Distance Between Terminals: 0.192 inches Drive Level Rating: Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.003/+0.003 Equivalent Resistance Value In Ohms: 60.0

N/a

NSN 5955-00-057-2746

Quartz Crystal Unit - Page 2 of 2



		• •			
ш	ın	10	<i>(</i>)+	Measure:	

--

Demilitarization:

No

Fiig:

A059a0