## NSN 5955-00-060-0757

Quartz Crystal Unit - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5955-00-060-0757   |
|---|
| Overall Length:   |
| 0.630 inches  |
| Terminal Length:  |
| Between 0.090 inches and 0.100 inches   |
| Overall Width:  |
| 0.435 inches  |
| Body Length:  |
| 0.530 inches  |
| Body Width:   |
| 0.402 inches  |
| Body Thickness:   |
| 0.150 inches  |
| Overall Thickness:  |
| 0.183 inches  |
| Terminal Diameter:  |
| 0.040 inches  |
| Mode Of Oscillation:  |
| Third overtone  |
| Circuit Resonance:  |
| Series resonance  |
| Shunt Capacitance In Picofarads:  |
| 7.0   |
| Specified Frequency:  |
| 38.3333 megahertz   |
| Holder Cover Material:  |
| Metal   |
| Operating Tempurature Range:  |
| -55.0 to 105.0 degrees celsius  |
| Center To Center Distance Between Terminals:  |
| Between 0.190 inches and 0.194 centimeters  |
| Drive Level Rating:   |
| Between 2.0 milliwatts and 1.6 milliwatts and 2.4 milliwatts  |
| Frequency Tolerance For Operating Tempurature In Percent:   |
| -0.005 to 0.005   |
| Equivalent Resistance Value In Ohms:  |
| 40.0  |
| Style Designator:   |
| Oval body, pin terminals  |
| Test Data Document:   |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain         |

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/34 government specification

## NSN 5955-00-060-0757

Quartz Crystal Unit - Page 2 of 2



| _ |     |      |   |        |  |
|---|-----|------|---|--------|--|
| c | hο  | JIF. |   | .ife:  |  |
| J | 116 |      | _ | .II C. |  |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0