## NSN 5955-00-060-0759

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-060-0759

| Overall Length:   |
|---|
| Between 0.620 inches and 0.630 inches   |
| Terminal Length:  |
| Between 0.090 inches and 0.100 inches   |
| Overall Width:  |
| 0.435 inches  |
| Body Length:  |
| 0.530 inches  |
| Body Width:   |
| 0.402 inches  |
| Body Thickness:   |
| 0.150 inches  |
| Overall Thickness:  |
| 0.183 inches  |
| Terminal Diameter:  |
| Between 0.038 inches and 0.042 inches   |
| Mode Of Oscillation:  |
| Third overtone  |
| Circuit Resonance:  |
| Series resonance  |
| Shunt Capacitance In Picofarads:  |
| 7.0   |
| Specified Frequency:  |
| 38.40741 megahertz  |
| Holder Cover Material:  |
| Metal   |
| Operating Tempurature Range:  |
| -55.0 to 105.0 degrees celsius  |
| Center To Center Distance Between Terminals:  |
| Between 0.184 inches and 0.200 centimeters  |
| Drive Level Rating:   |
| Between 1.6 milliwatts and 2.4 milliwatts   |
| Frequency Tolerance For Operating Tempurature In Percent:   |
| -0.005/+0.005   |
| Equivalent Resistance Value In Ohms:  |
| 40.0  |
| Style Designator:   |
| Oval body, pin terminals  |
| Test Data Document:   |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/50 government specification

## NSN 5955-00-060-0759

Quartz Crystal Unit - Page 2 of 2



| _ |   |    | • |    |    |
|---|---|----|---|----|----|
| • | n | ο. | • | 18 | e: |
|   |   |    |   |    |    |

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0