NSN 5955-00-060-0767

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-060-0767

| Overall Length: |
|---|
| Between 0.620 inches and 0.630 inches |
| Terminal Length: |
| Between 0.090 inches and 0.100 inches |
| Overall Width: |
| 0.435 inches |
| Body Length: |
| 0.530 inches |
| Body Width: |
| 0.402 inches |
| Body Thickness: |
| 0.150 inches |
| Overall Thickness: |
| 0.183 inches |
| Terminal Diameter: |
| Between 0.038 inches and 0.042 inches |
| Mode Of Oscillation: |
| Third overtone |
| Circuit Resonance: |
| Series resonance |
| Shunt Capacitance In Picofarads: |
| 7.0 |
| Specified Frequency: |
| 38.7037 megahertz |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| -55.0 to 105.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.184 mils and 0.200 inches |
| Drive Level Rating: |
| Between 1.6 milliwatts and 2.4 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.005/+0.005 |
| Equivalent Resistance Value In Ohms: |
| 40.0 |
| Style Designator: |
| Oval body, pin terminals |
| Test Data Document: |
| 81349-mil-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |

81349-mil-c-3098/50 government specification

Specification Data:

NSN 5955-00-060-0767

Quartz Crystal Unit - Page 2 of 2



| Shelf Life: | She | lf | Life: |
|-------------|-----|----|-------|
|-------------|-----|----|-------|

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0