NSN 5955-00-060-0774

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-060-0774

| Overall Length: |
|---|
| Between 0.620 inches and 0.630 inches |
| Terminal Length: |
| Between 0.090 inches and 0.100 inches |
| Overall Width: |
| 0.435 inches |
| Body Length: |
| 0.530 inches |
| Body Width: |
| 0.402 inches |
| Body Thickness: |
| 0.150 inches |
| Overall Thickness: |
| 0.183 inches |
| Terminal Diameter: |
| Between 0.038 inches and 0.042 inches |
| Mode Of Oscillation: |
| Third overtone |
| Circuit Resonance: |
| Series resonance |
| Shunt Capacitance In Picofarads: |
| 7.0 |
| Specified Frequency: |
| 38.96296 megahertz |
| Holder Cover Material: |
| Metal |
| Operating Tempurature Range: |
| -55.0 to 105.0 degrees celsius |
| Center To Center Distance Between Terminals: |
| 0.184 mils and 0.200 inches |
| Drive Level Rating: |
| Between 1.6 milliwatts and 2.4 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.005/+0.005 |
| Equivalent Resistance Value In Ohms: |
| 40.0 |
| Style Designator: |
| Oval body, pin terminals |
| Test Data Document: |
| 81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/50 government specification

NSN 5955-00-060-0774

Quartz Crystal Unit - Page 2 of 2



| | | ife: | |
|--|--|------|--|
| | | | |
| | | | |

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0