# NSN 5955-00-060-0809

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-060-0809

# **Overall Length:**

Between 0.620 inches and 0.630 inches

# **Terminal Length:**

Between 0.090 inches and 0.100 inches

## **Overall Width:**

0.435 inches

#### **Body Length:**

0.530 inches

#### **Body Width:**

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

#### **Terminal Diameter:**

Between 0.038 inches and 0.042 inches

## Mode Of Oscillation:

Third overtone

#### **Circuit Resonance:**

Series resonance

# Shunt Capacitance In Picofarads:

7.0

## Specified Frequency:

41.48148 megahertz

## Holder Cover Material:

Metal

## **Operating Tempurature Range:**

-55.0 to 105.0 degrees celsius

## **Center To Center Distance Between Terminals:**

Between 0.184 inches and 0.200 centimeters

#### **Drive Level Rating:**

Between 1.6 milliwatts and 2.4 milliwatts

## Frequency Tolerance For Operating Tempurature In Percent:

-0.005/+0.005

## **Equivalent Resistance Value In Ohms:**

40.0

# Style Designator:

Oval body, pin terminals

## **Test Data Document:**

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/50 government specification

# NSN 5955-00-060-0809

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A059a0

