NSN 5955-00-060-0833

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-060-0833

view Offilite at https://aerobasegroup.com/his//5555-00-0005
Overall Length:
Between 0.620 inches and 0.630 inches
Terminal Length:
Between 0.090 inches and 0.100 inches
Overall Width:
0.435 inches
Body Length:
0.530 inches
Body Width:
0.402 inches
Body Thickness:
0.150 inches
Overall Thickness:
0.183 inches
Terminal Diameter:
Between 0.038 inches and 0.042 inches
Mode Of Oscillation:
Third overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
42.37037 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-55.0/+105.0 degrees celsius
Center To Center Distance Between Terminals:
0.184 mils and 0.200 inches
Drive Level Rating:
Between 1.6 milliwatts and 2.4 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.005 to 0.005
Equivalent Resistance Value In Ohms:
40.0
Style Designator:
Oval body, pin terminals
Test Data Document:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-3098/50 government specification

NSN 5955-00-060-0833

Quartz Crystal Unit - Page 2 of 2



_				-		
C	h	0	Iŧ.		ife:	

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A059a0