NSN 5955-00-061-1394

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-061-1394

Ove	erall	Len	gth	
Bet	wee	n 0.7	45	i
_	_			

Between 0.745 inches and 0.775 inches

Terminal Length:

Between 0.245 inches and 0.255 inches

Overall Width:

Between 0.408 inches and 0.428 inches

Body Length:

Between 0.500 inches and 0.525 inches

Body Width:

Between 0.394 inches and 0.401 inches

Body Thickness:

Between 0.142 inches and 0.149 inches

Overall Thickness:

Between 0.156 inches and 0.176 inches

Terminal Diameter:

Between 0.038 inches and 0.042 inches

Mode Of Oscillation:

Third overtone

Circuit Resonance:

Series resonance

Shunt Capacitance In Picofarads:

7.0

Specified Frequency:

25.720 megahertz

Holder Cover Material:

Metal

Operating Tempurature Range:

-40.0 to 65.0 degrees celsius

Center To Center Distance Between Terminals:

Between 0.184 inches and 0.200 inches

Drive Level Rating:

Between 1.6 milliwatts and 2.4 milliwatts

Frequency Tolerance For Operating Tempurature In Percent:

-0.0025 to 0.0025

Equivalent Resistance Value In Ohms:

40.0

Style Designator:

Oval body, pin terminals

Shelf Life:

N/a

Unit Of Measure:

--

NSN 5955-00-061-1394

Quartz Crystal Unit - Page 2 of 2



Demilitarization:

No

Fiig:

A059a0