

View Online at <https://aerobasegroup.com/nsn/5955-00-064-2152>

**Overall Length:**

0.710 inches

**Terminal Length:**

Between 0.220 inches and 0.280 inches

**Overall Width:**

Between 0.410 inches and 0.430 inches

**Body Length:**

Between 0.432 inches and 0.450 inches

**Body Width:**

Between 0.395 inches and 0.405 inches

**Body Thickness:**

Between 0.145 inches and 0.155 inches

**Overall Thickness:**

Between 0.160 inches and 0.180 inches

**Terminal Diameter:**

Between 0.038 inches and 0.042 inches

**Mode Of Oscillation:**

Fundamental

**Circuit Resonance:**

Antiresonance

**Load Capacitance In Picofarads:**

Between 31.5 and 32.5

**Shunt Capacitance In Picofarads:**

7.0

**Specified Frequency:**

11.375 megahertz

**Frequency Tolerance At Reference Temperature In Percent:**

-0.002/+0.002

**Frequency Stability In Percent:**

-0.0005 to 0.0005

**Controlled Reference Temp:**

85.0 degrees celsius

**Operable Temperature Range:**

-55.0/+80.0 degrees celsius

**Holder Cover Material:**

Metal

**Operating Temperature Range:**

+80.0 to 90.0 degrees celsius

**Center To Center Distance Between Terminals:**

Between 0.182 inches and 0.202 centimeters

**Drive Level Rating:**

Between 2.0 milliwatts and 3.0 milliwatts

**Frequency Tolerance For Operating Temperature In Percent:**

-0.002/+0.002

**Equivalent Resistance Value In Ohms:**

22.0

**Style Designator:**

Oval body, pin terminals

**Specification Data:**

81349-milc3098/85 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A059a0