## NSN 5955-00-078-6138

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-078-6138
Overall Length:
0.530 inches
Terminal Length:
Between 1.000 inches and 1.120 inches
Overall Width:
0.435 inches
Body Width:
0.402 inches
Body Thickness:
0.150 inches
Overall Thickness:
0.183 inches
Terminal Diameter:
Between 0.015 inches and 0.019 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 31.5 and 32.5
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
11.000 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
+20.0 to 70.0 degrees celsius
Center To Center Distance Between Terminals:
Between 0.184 inches and 0.200 inches
Drive Level Rating:
Between 2.0 milliwatts and 3.0 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.0025 to 0.0025
Equivalent Resistance Value In Ohms:
25.0
Style Designator:
Oval body, wire leads
Test Data Document:
81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/116 government specification

## NSN 5955-00-078-6138

Quartz Crystal Unit - Page 2 of 2



		ife:	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0