## NSN 5955-00-078-7752

Quartz Crystal Unit - Page 1 of 2

**Overall Length:** 

Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/5955-00-078-7752

0.530 inches
Terminal Length:
1.500 inches
Overall Width:
0.435 inches
Body Width:
0.402 inches
Body Thickness:
0.150 inches
Overall Thickness:
0.183 inches
Terminal Diameter:
0.017 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 30.0 and 29.5 and 30.5
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
20.100 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-55.0 to 105.0 degrees celsius
Center To Center Distance Between Terminals:
0.192 inches
Drive Level Rating:
Between 5.0 milliwatts and 4.0 milliwatts and 6.0 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.002/+0.002 and -0.003 to 0.003
Equivalent Resistance Value In Ohms:
25.0
Style Designator:
Oval body, wire leads
Test Data Document:
81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical" "avorage" "" atc.)

## NSN 5955-00-078-7752

Quartz Crystal Unit - Page 2 of 2



			ure:	

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0