# NSN 5955-00-078-7756

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-078-7756

Overall Length:

0.530 inches

**Terminal Length:** 

0.500 inches

# **Overall Width:**

0.435 inches

## Body Width:

0.402 inches

#### Body Thickness:

0.150 inches

#### **Overall Thickness:**

0.183 inches

**Terminal Diameter:** 

Between 0.016 inches and 0.019 inches

## Mode Of Oscillation:

Fundamental

#### **Circuit Resonance:**

Antiresonance

## Load Capacitance In Picofarads:

Between 29.5 and 30.5

## Shunt Capacitance In Picofarads:

7.0

#### Specified Frequency:

20.400 megahertz

## Holder Cover Material:

Metal

## **Operating Tempurature Range:**

-55.0 to 105.0 degrees celsius

## Center To Center Distance Between Terminals:

Between 0.184 inches and 0.200 inches

#### **Drive Level Rating:**

Between 4.0 milliwatts and 6.0 milliwatts

## Frequency Tolerance For Operating Tempurature In Percent:

-0.002 to 0.002 and -0.003 to 0.003

## **Equivalent Resistance Value In Ohms:**

25.0

## Style Designator:

Oval body, wire leads

## **Test Data Document:**

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/47 government specification

# NSN 5955-00-078-7756

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

