## NSN 5955-00-082-3138

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-082-3138

**Overall Length:** 

1.023 inches

**Terminal Length:** 

0.238 inches

**Overall Width:** 

0.757 inches

Body Length:

0.775 inches

**Body Width:** 

0.725 inches

Body Thickness:

0.317 inches

**Overall Thickness:** 

0.352 inches

**Terminal Diameter:** 

#### 0.050 inches

Mode Of Oscillation:

Fundamental

**Circuit Resonance:** 

Antiresonance

Load Capacitance In Picofarads:

Between 32.0 and 31.5 and 32.5

Shunt Capacitance In Picofarads:

7.0

#### Specified Frequency:

12.155 megahertz

Holder Cover Material:

Metal

**Operating Tempurature Range:** 

-55.0 to 105.0 degrees celsius

**Center To Center Distance Between Terminals:** 

0.486 inches

**Drive Level Rating:** 

Between 5.0 milliwatts and 4.0 milliwatts and 6.0 milliwatts

#### Frequency Tolerance For Operating Tempurature In Percent:

-0.005 to 0.005

**Equivalent Resistance Value In Ohms:** 

22.0

Style Designator:

Oval body, pin terminals

### **Test Data Document:**

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

# NSN 5955-00-082-3138

Quartz Crystal Unit - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fiig:

A059a0

