## NSN 5955-00-082-3967

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-082-3967

view Offilite at https://defobasegroup.com/his//0000-002-000/
Overall Length:
Between 0.998 inches and 1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Fifth overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
54.850 megahertz
Holder Cover Material:
Metal
Operating Tempurature Range:
-55.0 to 105.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Rating:
Between 1.6 milliwatts and 2.4 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.005/+0.005
Equivalent Resistance Value In Ohms:
50.0
Style Designator:
Oval body, pin terminals
Test Data Document:

81349-mil-c-3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## **Specification Data:**

81349-mil-c-3098/32 government specification

## NSN 5955-00-082-3967

Quartz Crystal Unit - Page 2 of 2



	Life:

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0