NSN 5955-00-082-4456

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-082-4456

Overall Length:			
1.023 inches			
Terminal Length:			
Between 0.223 inches and 0.248 inches			
Overall Width:			
0.757 inches			
Body Length:			
0.775 inches			
Body Width:			
0.725 inches			
Body Thickness:			
0.317 inches			
Overall Thickness:			
0.352 inches			
Terminal Diameter:			
Between 0.048 inches and 0.052 inches			
Mode Of Oscillation:			
Third overtone			
Circuit Resonance:			
Series resonance			
Shunt Capacitance In Picofarads:			
7.0			
Specified Frequency:			
43.18519 megahertz			
Frequency Tolerance At Reference Tempurature In Percent:			
-0.007 to 0.007			
Frequency Stability In Percent:			
-0.00025/+0.00025			
Controlled Reference Temp:			
75.0 degrees celsius			
Operable Tempurature Range:			
-55.0/+90.0 degrees celsius			
Holder Cover Material:			
Metal			
Operating Tempurature Range:			
+70.0 to 80.0 degrees celsius			
Center To Center Distance Between Terminals:			
0.478 mils and 0.494 inches			
Drive Level Rating:			
Between 0.8 milliwatts and 1.2 milliwatts			

Frequency Tolerance For Operating Tempurature In Percent:

-0.001/+0.001

NSN 5955-00-082-4456

Quartz Crystal Unit - Page 2 of 2



E	Equivalent Resistance Value In Ohms:	
4	0.0	
S	Style Designator:	
C	Oval body pin terminals	

Test Data Document:

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf	Life:
N/a	

Unit Of Measure:

Demilitarization:

No

Fiig:

A059a0