

View Online at <https://aerobasegroup.com/nsn/5955-00-087-7897>

**Overall Length:**

1.023 inches

**Terminal Length:**

0.238 inches

**Overall Width:**

0.757 inches

**Body Length:**

0.775 inches

**Body Width:**

0.725 inches

**Body Thickness:**

0.317 inches

**Overall Thickness:**

0.352 inches

**Terminal Diameter:**

0.050 inches

**Mode Of Oscillation:**

Fundamental

**Circuit Resonance:**

Antiresonance

**Load Capacitance In Picofarads:**

Between 32.0 and 31.5 and 32.5

**Shunt Capacitance In Picofarads:**

7.0

**Specified Frequency:**

17.000 megahertz

**Frequency Tolerance At Reference Temperature In Percent:**

-0.007 to 0.007

**Frequency Stability In Percent:**

-0.0005/+0.0005

**Controlled Reference Temp:**

75.0 degrees celsius

**Operable Temperature Range:**

-55.0 to 90.0 degrees celsius

**Holder Cover Material:**

Metal

**Operating Temperature Range:**

+70.0 to 80.0 degrees celsius

**Center To Center Distance Between Terminals:**

0.486 inches

**Drive Level Rating:**

Between 2.5 milliwatts and 2.0 milliwatts and 3.0 milliwatts

**Frequency Tolerance For Operating Temperature In Percent:**

-0.002/+0.002

**Equivalent Resistance Value In Ohms:**

20.0

**Style Designator:**

Oval body, pin terminals

**Test Data Document:**

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A059a0