## NSN 5955-00-114-7860

Pulse Delay Oscillator - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-114-7860

Overall Length:
3.250 inches
Overall Height:
0.750 inches
Overall Width:
0.750 inches
Environmental Protection:
Weatherproof
Vibration Resistance Range In Hertz: +5.0 to 1000.0
Vibration Resistance Amplitude:
8.0 gravitational units
Shock Resistance Rating In Gravitational Units:
15.0
Operating Tempurature Range:
-45.0 to 85.0 degrees celsius
Average Life Rating:
50000.0
Average Life Measurement:
Hours
Average Life Rating In Hours:
50000.0
Basic Shape Style:
Rectangular or square
Maximum Operating Altitude Rating:
70000.0 feet
Inclosure Type:
Encased
Installation Design:
Mechanical
Pulse Duration Per Channel:
0.500 microseconds operating channel and 3.000 microseconds operating channel
Pulse Rise Time Per Channel:
50.000 nanoseconds operating channel
Pulse Decay Time Per Channel:
100.000 nanoseconds operating channel
Shock Pulse Duration Time:
11.0 milliseconds
Connection Type And Location:
Receptacle, coaxial left side and receptacle, coaxial right side
Connection Contact Type And Quantity:
2 receptacle, coaxial internal

## NSN 5955-00-114-7860

Pulse Delay Oscillator - Page 2 of 2

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

Yes - demil/mli

Fiig:

A32200

