

View Online at <https://aerobasegroup.com/nsn/5955-00-120-0512>

Overall Length:

3.750 inches

Overall Height:

2.234 inches

Environmental Protection:

Pressurized

Vibration Resistance Range In Hertz:

+10.0 to 2000.0

Vibration Resistance Amplitude:

0.5 gravitational units and 20.0 inches total excursion

Shock Resistance Rating In Gravitational Units:

60.0

Operating Temperature Range:

+10.0 to 40.0 degrees celsius

Average Life Measurement:

Indefinite

End Application:

Lgm-30 minuteman

Basic Shape Style:

Rectangular or square

Maximum Operating Altitude Rating:

Not rated

Inclosure Type:

Hermetically sealed

Installation Design:

Mechanical

Circuit Construction Type:

Solid state

Frequency Per Channel:

9.984 megahertz output channel

Attenuation In Decibels:

Not rated

Signal Voltage Rating Per Channel:

2.000 volts output

Overall Gain:

Not rated

Impedance Rating Per Channel:

Not rated

Shock Pulse Duration Time:

11.0 milliseconds

Connection Type And Location:

Receptacle, power bottom

Connection Contact Type And Quantity:

9 receptacle, power internal

External Dc Operating Voltage In Volts:

5.0 1st voltage

Criticality Code Justification:

Feat

Special Features:

Design analysis

Nuclear Hardness Critical Feature:

Hardened

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A32200