## NSN 5955-00-127-9899

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-127-9899

Overall Length:
1.023 inches
Terminal Length:
Between 0.223 inches and 0.248 inches
Overall Width:
0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 31.5 and 32.5
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
10.16667 megahertz
Frequency Tolerance At Reference Tempurature In Percent:
-0.007 to 0.007
Frequency Stability In Percent:
-0.0005/+0.0005
Controlled Reference Temp:
75.0 degrees celsius
Operable Tempurature Range:
-55.0/+90.0 degrees celsius
Holder Cover Material:
Metal
Operating Tempurature Range:
+70.0 to 80.0 degrees celsius
Center To Center Distance Between Terminals:
Between 0.478 inches and 0.494 centimeters
Drive Level Rating:

Between 4.0 milliwatts and 6.0 milliwatts

## NSN 5955-00-127-9899

Quartz Crystal Unit - Page 2 of 2



Frequency Tolerance For Operating Tempurature In Percent	Frequency	Tolerance Fo	r Operating	<b>Tempurature In Percent</b>
--	-----------	--------------	-------------	-------------------------------

-0.002/+0.002

**Equivalent Resistance Value In Ohms:** 

35.0

**Style Designator:** 

Oval body, pin terminals

**Test Data Document:** 

81349-milc3098-9 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Shelf Life:

N/a

**Unit Of Measure:** 

--

**Demilitarization:** 

No

Fiig:

A059a0