NSN 5955-00-128-8475

Quartz Crystal Unit - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5955-00-128-8475

| Overall Le | ngth: |
|-------------|--|
| 1.593 inche | 95 |
| Terminal L | ength: |
| 0.468 inche | 95 |
| Overall Wi | dth: |
| Between 0. | 797 inches and 0.827 inches |
| Body Leng | yth: |
| Between 1. | 110 inches and 1.140 inches |
| Overall Th | ickness: |
| Between 0. | 407 inches and 0.447 inches |
| Terminal D | Diameter: |
| Between 0. | 091 inches and 0.095 inches |
| Mode Of O | scillation: |
| Fundament | tal |
| Circuit Res | sonance: |
| Antiresona | nce |
| Load Capa | citance In Picofarads: |
| 13.0 | |
| Specified I | Frequency: |
| 8.0167 me | gahertz |
| Holder Co | ver Material: |
| Plastic | |
| Operating | Tempurature Range: |
| -40.0/+70.0 |) degrees celsius |
| Center To | Center Distance Between Terminals: |
| 0.486 inche | es |
| Frequency | Tolerance For Operating Tempurature In Percent: |
| -0.020/+0.0 | 020 |
| Equivalent | Resistance Value In Ohms: |
| 50.0 | |
| Style Desig | gnator: |
| Rectangula | r body, pin terminals |
| Test Data | Document: |
| 81349-milc | 10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; exc | cludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmer | ntal and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Shelf Life: | |
| N/a | |
| Unit Of Me | asure: |
| | |
| Demilitariz | ation: |
| Yes - demil | /mli |
| Fiig: | |

A059a0