## NSN 5955-00-129-5741

Quartz Crystal Unit - Page 1 of 2

AeroBase Group

View Online at https://aerobasegroup.com/nsn/5955-00-129-5741

<ul> <li>1.53 inches</li> <li>Terninal Length:</li> <li>0.468 inches</li> <li>Overal Width:</li> <li>Between 0.797 inches and 0.827 inches</li> <li>Body Length:</li> <li>Between 0.797 inches and 0.827 inches</li> <li>Body Length:</li> <li>Between 0.797 inches and 0.427 inches</li> <li>Body Length:</li> <li>Between 0.477 inches and 0.447 inches</li> <li>Coveral Width:</li> <li>Between 0.407 inches and 0.447 inches</li> <li>Terninal Diameter:</li> <li>Between 0.407 inches and 0.955 inches</li> <li>Mode Of Scillation:</li> <li>Fundamental</li> <li>Circuit Resonance</li> <li>Lead Capacitance In Picofarads:</li> <li>13.0</li> <li>Specified Frequency:</li> <li>8.3667 megahertz</li> <li>Holder Cover Material:</li> <li>Plastic</li> <li>Operating Tempurature Range:</li> <li>4.010 for 0. degrees celsius</li> <li>Circuit Resistance Value In Ohms:</li> <li>3.00 milliwatts</li> <li>Frequency Tolerance For Operating Tempurature In Percent:</li> <li>4.020 to 0.020</li> <li>Equivalent Resistance Value In Ohms:</li> <li>5.00</li> <li>Syle Designator:</li> <li>Restangular body, pin terminals</li> <li>Test Data Document</li> <li>State Data Document and test conditions that are shown as "ypical", "average", ", etc.).</li> </ul>	Overall Length:	
0.468 inches Overall Widh: Between 0.797 inches and 0.827 inches Body Length: Between 0.791 inches and 1.140 inches Doreall Thickness: Between 0.407 inches and 0.147 inches Terminal Diameter: Between 0.407 inches and 0.447 inches Terminal Diameter: Between 0.991 inches and 0.995 inches Mode Of Oscillation: Fundamental Circuit Resonance: Antiresonance Load Capacitance In Picofarads: 13.0 Specified Frequency: 8.3667 megahertz Holder Cover Material: Plastic Operating Tempurature Range: -0.010 r0.01 degrees celsius Circuit Resonance Between Terminals: 0.408 inches Drive Level Rating: 0.300 Specified Frequency: 0.3085 Frequency Tolerance Between Terminals: 0.486 inches Drive Level Rating: 0.300 miliwatts Frequency Tolerance Capacitance In Picofaria Depresent: -0.2010 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Beignator: Restangular body, pin terminals Tert Data Document: 81349-mile-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain 2011 frequency interminals centains and interval publications, reflecting general type data on certain 2012 frequency milications (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain 2014 frequency milications (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain 2014 frequency milications (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain 2014 frequency milications (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain 2014 frequency milications (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain 2014 frequency milications (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain 2014 frequency milications (includes engineering type bulletins, brochures, etc., that refl	1.593 inches	
Overall Width:         Between 0.797 inches and 0.827 inches         Body Length:         Between 1.110 inches and 1.140 inches         Overall Thickness:         Between 0.407 inches and 0.447 inches         Terminal Diameter:         Between 0.091 inches and 0.095 inches         Mode Of Oscillation:         Fundamental         Circuit Resonance:         Antiresonance         Load Capacitance In Picofarads:         13.0         Specified Frequency:         8.3667 megahentz         Holder Cover Material:         Plastic         Operating Tempurature Range:         +40.0 to 70.0 degrees celsius         Center To Center Distance Between Terminals:         0.408 inches         Drive Level Rating:         0.400 milliwatts         Frequency Tolerance For Operating Tempurature In Percent:         -0.020 to 0.020         Equivalent Resistance Value In Ohms:         0.03         Style Besignator:         Rectangular body, pin terminals         Test Data Document:         8149-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data on certain	Terminal Length:	
Between 0.797 inches and 0.827 inches         Between 1.110 inches and 1.140 inches         Between 1.110 inches and 1.140 inches         Between 0.407 inches and 0.447 inches         Terminal Diametr:         Between 0.091 inches and 0.095 inches         Mode Of Oscillation:         Fundamental         Circuit Resonance:         Antiresonance         Load Capacitance In Picofarads:         13.0         Specified Frequency:         8.3667 megahertz         Holder Cover Material:         Plastic         Operating Tempurature Range:         -40.0 to 70.0 degrees celsius         Center To Center Distance Between Terminals:         0.496 inches         Drive Level Rating:         -0.200 to 0.020         Equivalent Resistance Value In Ohms:         -0.30         Style Designator:         Rectangular body, pin terminals         Catearupt Designator:         Projoupt Designator:         -0.201 to 0.020         Explanet Resistance Value In Ohms:         -0.30         Style Designator:         Rectangular body, pin terminals         Text Data Document:         81349-mil-c-10405 specification (includes engineering type bull	0.468 inches	
Body Length:         Between 1.110 inches and 1.140 inches         Overall Thickness:         Between 0.407 inches and 0.447 inches         Terminal Dameter:         Between 0.091 inches and 0.095 inches         Mode Of Oscillation:         Fundamental         Circuit Resonance:         Antiresonance         Load Capacitance In Picofarads:         13.0         Specified Frequency:         8.3667 megahertz         Holder Cover Material:         Plastic         Operating Tempurature Range:         4.00 to 70.0 degrees celsius         Conter Distance Between Terminals:         0.486 inches         Drive Level Rating:         0.200 milliwats         Frequency Tolerance For Operating Tempurature In Percent:         0.020 to 0.020         Equivalent Resistance Value In Ohms:         0.02         Specification conclustes         Specification body, pin terminals         Terminals         Concluster Distance Evener         10.00         Specification type data engineering type bulletins, brochures, etc., that reflect specification type data engelific formation specification type data engelific formation specification type data engelific formatin excludes commercial catalogs, industry directories, a	Overall Width:	
Between 1.100 inches and 1.140 inches Overall Thickness: Between 0.407 inches and 0.447 inches Termial Diameter: Between 0.091 inches and 0.095 inches Mode Of Oscillation: Fundamental Circuit Resonance Circuit Circui	Between 0.797 inches a	nd 0.827 inches
Overall Thickness:         Between 0.407 inches and 0.447 inches         Terminal Diameter:         Between 0.091 inches and 0.095 inches         Mode Of Oscillation:         Fundamental         Circuit Resonance:         Antiresonance         Load Capacitance In Picofarads:         13.0         Specified Frequency:         8.3667 megahertz         Holder Cover Material:         Plastic         Operating Tempurature Range:         -0.0.0.0.0 degrees celsius         Center To Center Distance Between Terminals:         0.486 inches         Drive Level Rating:         3.0.0         Stop 0.020         Equatent Resistance Value In Ohms:         0.020         Style Designator:         Rectanguiar tody, pin terminals         Colo         Style Designator:         Rectanguiar tody, pin terminals         Colo         Style Designator:         Rectanguiar tody, pin terminals         Core To Isona Colo (includes engineering type bulletins, brochures, etc., that reflect specification type data on certair	Body Length:	
Between 0.407 inches and 0.447 inches Terminal Diameter: Between 0.091 inches and 0.095 inches Mode Of Oscillation: Fundamental Clrcuit Resonance: Clrcuit Resonance: Clocuit Resonance: Clocuit Resonance: Clocuit Resonance Clocui	Between 1.110 inches a	nd 1.140 inches
Terminal Diameter: Between 0.091 inches and 0.095 inches Mode Of Oscillation: Fundamental Circuit Resonance: Antiresonance Load Capacitance In Picofarads: 13.0 Specified Frequency: 8.3667 megahertz Holder Cover Material: Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-o-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Overall Thickness:	
Between 0.091 inches and 0.095 inches Mode Of Oscillation: Fundamental Circuit Resonance: Antiresonance Load Capacitance In Picofarads: 13.0 Specified Frequency: 8.3667 megahertz Holder Cover Material: Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.202 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format, excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Between 0.407 inches a	nd 0.447 inches
Mode Of Oscillation:         Fundamental         Circuit Resonance:         Antiresonance         Load Capacitance In Picofarads:         13.0         Specified Frequency:         8.3667 megahertz         Holder Cover Material:         Plastic         Operating Tempurature Range:         +0.0 for 0.0 degrees celsius         Center To Center Distance Between Terminals:         0.486 inches         Drive Level Rating:         0.0 onilliwatts         Frequency Tolerance For Operating Tempurature In Percent:         -0.200 to 0.20         Equivalent Resistance Value In Ohms:         50.0         Style Designator:         Rectangular body, pin terminals         Text Data Document:         8149-mil-e-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific formar; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Terminal Diameter:	
Fundamental         Circuit Resonance:         Antiresonance         Load Capacitance In Picofarads:         13.0         Specified Frequency:         8.3667 megahertz         Holder Cover Material:         Plastic         Operating Tempurature Range:         -40.0 to 70.0 degrees celsius         Center To Center Distance Between Terminals:         0.486 inches         Drive Level Rating:         30.0 milliwatts         Frequency Tolerance For Operating Tempurature In Percent:         -0.020 to 0.020         Equivalent Resistance Value In Ohms:         50.0         Style Designator:         Rectangular body, pin terminals         Test Data Document:         81349-mil-e-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Between 0.091 inches a	nd 0.095 inches
Circuit Resonance: Antiresonance Load Capacitance In Picofarads: 13.0 Specified Frequency: 8.3667 megahertz Holder Cover Material: Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -44.0 to 70.0 degrees celsius -44.0 to 70.0 to 70.0 degrees celsius -44.0 to 70.0 t	Mode Of Oscillation:	
Antiresonance Load Capacitance In Picofarads: 13.0 Specified Frequency: 8.3667 megahertz Holder Cover Material: Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Fundamental	
Load Capacitance In Picofarads: 13.0 Specified Frequency: 8.3667 megahertz Holder Cover Material: Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Ter Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Circuit Resonance:	
13.0 Specified Frequency: 8.3667 megahertz Holder Cover Material: Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Antiresonance	
Specified Frequency: 8.3667 megahertz Holder Cover Material: Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Load Capacitance In P	cofarads:
8.3667 megahertz Holder Cover Material: Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific rorrat; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	13.0	
Holder Cover Material: Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Specified Frequency:	
Plastic Operating Tempurature Range: -40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	8.3667 megahertz	
Operating Tempurature Range:         -40.0 to 70.0 degrees celsius         Center To Center Distance Between Terminals:         0.486 inches         Drive Level Rating:         30.0 milliwatts         Frequency Tolerance For Operating Tempurature In Percent:         -0.020 to 0.020         Equivalent Resistance Value In Ohms:         50.0         Style Designator:         Rectangular body, pin terminals         Test Data Document:         81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Holder Cover Material:	
-40.0 to 70.0 degrees celsius Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Plastic	
Center To Center Distance Between Terminals: 0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Operating Tempurature	Range:
0.486 inches Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific	-40.0 to 70.0 degrees ce	sius
Drive Level Rating: 30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Center To Center Dista	nce Between Terminals:
30.0 milliwatts Frequency Tolerance For Operating Tempurature In Percent: -0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	0.486 inches	
Frequency Tolerance For Operating Tempurature In Percent: <ul> <li>-0.020 to 0.020</li> </ul> Equivalent Resistance Value In Ohms: <ul> <li>50.0</li> </ul> Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Drive Level Rating:	
-0.020 to 0.020 Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	30.0 milliwatts	
Equivalent Resistance Value In Ohms: 50.0 Style Designator: Rectangular body, pin terminals Test Data Document: 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Frequency Tolerance F	or Operating Tempurature In Percent:
50.0 <b>Style Designator:</b> Rectangular body, pin terminals <b>Test Data Document:</b> 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	-0.020 to 0.020	
Style Designator:         Rectangular body, pin terminals         Test Data Document:         81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Equivalent Resistance	Value In Ohms:
Rectangular body, pin terminals <b>Test Data Document:</b> 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	50.0	
<b>Test Data Document:</b> 81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Style Designator:	
81349-mil-c-10405 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specific format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Rectangular body, pin te	rminals
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain	Test Data Document:	
	81349-mil-c-10405 spec	fication (includes engineering type bulletins, brochures, etc., that reflect specification type data in specificatior
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).	format; excludes comme	rcial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
	environmental and perfo	mance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:	Specification Data:	
81349-mil-c-10405/5 government specification	81349-mil-c-10405/5 gov	ernment specification
Shelf Life:	Shelf Life:	
N/a	N/a	

---

## NSN 5955-00-129-5741

Quartz Crystal Unit - Page 2 of 2

Demilitarization:

No

Fiig:

A059a0

