## NSN 5955-00-147-3244

Quartz Crystal Unit - Page 1 of 2

Shelf Life:

N/a



View Online at https://aerobasegroup.com/nsn/5955-00-147-3244

Overall Length:					
1.937 inches					
Terminal Length:					
Between 0.625 inches and 0.655 inches					
Overall Width:					
1.170 inches					
Body Length:					
1.282 inches					
Body Width:					
1.125 inches					
Body Thickness:					
0.411 inches					
Overall Thickness:					
0.460 inches					
Terminal Diameter:					
Between 0.123 inches and 0.127 inches					
Mode Of Oscillation:					
Fundamental					
Circuit Resonance:					
Antiresonance					
Load Capacitance In Picofarads:					
Between 34.5 and 35.5					
Specified Frequency:					
8.00769 megahertz					
Holder Cover Material:					
Metal					
Operating Tempurature Range:					
-55.0/+90.0 degrees celsius					
Center To Center Distance Between Terminals:					
Between 0.490 inches and 0.510 centimeters					
Drive Level Rating:					
Between 27.0 milliwatts and 33.0 milliwatts					
Frequency Tolerance For Operating Tempurature In Percent:					
-0.005 to 0.005					
Equivalent Resistance Value In Ohms:					
30.0					
Style Designator:					
Oval body, pin terminals					
Test Data Document:					
81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;					
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental					
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).					

## NSN 5955-00-147-3244

Quartz Crystal Unit - Page 2 of 2



	ι	Jn	it	Of	Measure:
--	---	----	----	----	----------

--

Demilitarization:

No

Fiig:

A059a0

Mil-std (military Standard):

Mil-c-16 spec.