## NSN 5955-00-181-0469

Quartz Crystal Unit - Page 1 of 2

Between 0.223 inches and 0.248 inches

Overall Length: 1.023 inches Terminal Length:

Overall Width:
0.757 inches
Body Length:
0.775 inches



View Online at https://aerobasegroup.com/nsn/5955-00-181-0469

Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Fundamental
Circuit Resonance:
Antiresonance
Load Capacitance In Picofarads:
Between 31.5 and 32.5
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
7.761111 megahertz
Frequency Stability In Percent:
-0.0005/+0.0005
Controlled Reference Temp:
75.0 degrees celsius
Operable Tempurature Range:
-55.0/+90.0 degrees celsius
Holder Cover Material:
Metal or glass
Operating Tempurature Range:
+70.0/+80.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Rating:
Between 4.0 milliwatts and 6.0 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.002/+0.002 and -0.005 to 0.005

## NSN 5955-00-181-0469

Quartz Crystal Unit - Page 2 of 2

**Fiig:** A059a0



Equivalent Resistance Value In Ohms:
24.0
Style Designator:
Square body
Test Data Document:
81349-milc3098-30 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No