

NSN 5955-00-201-6111 Noncrystal Controlled Oscillator - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5955-00-201-6111 **Overall Length:** 8.125 inches **Overall Height:** 6.000 inches **Overall Width:** 8.000 inches **Vibration Resistance Range In Hertz:** Not rated **Shock Resistance Rating In Gravitational Units:** Not rated **Operating Tempurature Range:** Not rated **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Maximum Operating Altitude Rating:** Not rated **Inclosure Type:** Encased **Operating Control Method:** Manual Installation Design: Top of cabinet/counter **Control Type:** Local **Circuit Construction Type:** Solid state

Frequency Per Channel:

50.0 kilohertz operating channel

**Frequency Adjustment Type:** 

Continuous

**Attenuation In Decibels:** 

20.0

**Average Power Rating Per Channel:** 

Not rated

Signal Voltage Rating Per Channel:

5.000 volts output

**Overall Gain:** 

Not rated

Impedance Rating Per Channel:

600.000 ohms output channel

## NSN 5955-00-201-6111

A32200

Noncrystal Controlled Oscillator - Page 2 of 2



| Distortion Type And Percent:  |
|---|
| 0.5 frequency   |
| Maximum Continuous Operating Time In Hours:                                       |
| Not rated   |
| Operating Ac Frequency In Hertz:  |
| 50.0 1st voltage and 400.0 1st voltage and 50.0 2nd voltage and 400.0 2nd voltage |
| External Ac Operating Voltage In Volts:   |
| 250.0 2nd voltage   |
| Phase:  |
| Single  |
| Shelf Life:   |
| N/a   |
| Unit Of Measure:  |
|   |
| Demilitarization:   |
| No  |
| Fiig:   |