## NSN 5955-00-216-4313

Quartz Crystal Unit - Page 1 of 2

Between 0.223 inches and 0.248 inches

Overall Length: 1.023 inches

**Terminal Length:** 

**Overall Width:** 



View Online at https://aerobasegroup.com/nsn/5955-00-216-4313

0.757 inches
Body Length:
0.775 inches
Body Width:
0.725 inches
Body Thickness:
0.317 inches
Overall Thickness:
0.352 inches
Terminal Diameter:
Between 0.048 inches and 0.052 inches
Mode Of Oscillation:
Third overtone and fifth overtone
Circuit Resonance:
Series resonance
Shunt Capacitance In Picofarads:
7.0
Specified Frequency:
28.71111 megahertz
Frequency Stability In Percent:
-0.00025/+0.00025
Controlled Reference Temp:
75.0 degrees celsius
Operable Tempurature Range:
-55.0/+90.0 degrees celsius
Holder Cover Material:
Metal or glass
Operating Tempurature Range:
+70.0/+80.0 degrees celsius
Center To Center Distance Between Terminals:
0.478 mils and 0.494 centimeters
Drive Level Rating:
Between 0.8 milliwatts and 1.2 milliwatts
Frequency Tolerance For Operating Tempurature In Percent:
-0.001/+0.001 and -0.003/+0.003
Equivalent Resistance Value In Ohms:
40.0

## NSN 5955-00-216-4313

Quartz Crystal Unit - Page 2 of 2



Style	Desi	gnator:
Otylo	DCSI	gnator.

Square body

## **Test Data Document:**

81349-milc3098/28 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

O:		
She	IT	ITP:

N/a

**Unit Of Measure:** 

\_\_\_

Demilitarization:

No

Fiig:

A059a0