## NSN 5955-00-217-1286

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-217-1286			
Overall Length:			
1.023 inches			
Terminal Length:			
Between 0.223 inches and 0.248 inches			
Overall Width:			
0.757 inches			
Body Length:			
0.775 inches			
Body Width:			
0.725 inches			
Body Thickness:			
0.317 inches			
Overall Thickness:			
0.352 inches			
Terminal Diameter:			
Between 0.048 inches and 0.052 inches			
Mode Of Oscillation:			
Fundamental			
Circuit Resonance:			
Antiresonance			
Load Capacitance In Picofarads:			
Between 31.5 and 32.5			
Shunt Capacitance In Picofarads:			
7.0			
Specified Frequency:			
4.975 megahertz			
Holder Cover Material:			
Metal			
Operating Tempurature Range:			
-55.0/+105.0 degrees celsius			
Center To Center Distance Between Terminals:			
0.478 mils and 0.494 centimeters			
Drive Level Rating:			
Between 8.0 milliwatts and 12.0 milliwatts			
Frequency Tolerance For Operating Tempurature In Percent:			
-0.005/+0.005			
Equivalent Resistance Value In Ohms:			
60.0			
Style Designator:			
Oval body, pin terminals			
Test Data Document:			

81349-milc3098 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

## NSN 5955-00-217-1286

Quartz Crystal Unit - Page 2 of 2



She	lf	Life:	
Oile	••	LIIV.	

N/a

**Unit Of Measure:** 

--

Demilitarization:

No

Fiig:

A059a0