NSN 5955-00-224-5287

185.0 watts input

Noncrystal Controlled Oscillator - Page 1 of 2

View Online at https://aerobasegroup.com/nsn/5955-00-224-5287



Overall Length: 21.500 inches **Overall Height:** 13.000 inches **Overall Width:** 16.875 inches **Environmental Protection:** Moisture proof **Vibration Resistance Range In Hertz:** +10.0 to 55.0 **Individual Section Quantity: Operating Tempurature Range:** -40.0 to 131.0 degrees fahrenheit **Average Life Measurement:** Not rated **Basic Shape Style:** Rectangular or square **Identification Designator:** 0-39ctra7-80058 **Maximum Operating Altitude Rating:** 10000.0 feet **Inclosure Type:** Encased **Operating Control Method:** Manual Installation Design: Free-standing **Control Type:** Local **Circuit Construction Type:** Electron tube Frequency Shift: 850.0 hertz Frequency Per Channel: **Frequency Adjustment Type:** Continuous **Attenuation In Decibels:** Not rated **Average Power Rating Per Channel:**

NSN 5955-00-224-5287

Noncrystal Controlled Oscillator - Page 2 of 2



| Signal Voltage Rating Per Channel: |
|---|
| 44.000 volts output and 100.000 volts output |
| Overall Gain: |
| Not rated |
| Impedance Rating Per Channel: |
| 33.000 kilohms output channel |
| Distortion Type And Percent: |
| 5.0 phase |
| Indicator Device Type And Quantity: |
| 1 headset and 3 light |
| Maximum Continuous Operating Time In Hours: |
| Not rated |
| Connection Type And Location: |
| Single panel jack front and receptacle, power front |
| Operating Ac Frequency In Hertz: |
| 50.0 single voltage and 60.0 single voltage |
| External Ac Operating Voltage In Volts: |
| 115.0 single voltage |
| Phase: |
| Single |
| Fsc Application Data: |
| Radio teletypewriter set group for radio set anmrc2 |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| Yes - demil/mli |
| |

Fiig: A32200