

View Online at <https://aerobasegroup.com/nsn/5955-00-232-3058>

**Overall Length:**

0.530 inches

**Terminal Length:**

Between 0.630 inches and 0.750 inches

**Overall Width:**

0.435 inches

**Body Width:**

Between 0.380 inches and 0.402 inches

**Body Thickness:**

0.150 inches

**Overall Thickness:**

0.183 inches

**Terminal Diameter:**

Between 0.016 inches and 0.019 inches

**Mode Of Oscillation:**

Fundamental

**Circuit Resonance:**

Antiresonance

**Load Capacitance In Picofarads:**

Between 31.5 and 32.5

**Shunt Capacitance In Picofarads:**

Between 2.5 and 3.5

**Specified Frequency:**

3.315 megahertz

**Holder Cover Material:**

Metal or glass

**Operating Temperature Range:**

-35.0/+70.0 degrees celsius and -55.0/+90.0 degrees celsius

**Center To Center Distance Between Terminals:**

0.184 mils and 0.200 centimeters

**Drive Level Rating:**

2.0 milliwatts

**Frequency Tolerance For Operating Temperature In Percent:**

-0.0025/+0.0025 and -0.005/+0.005

**Equivalent Resistance Value In Ohms:**

150.0

**Style Designator:**

Oval body, pin terminals

**Test Data Document:**

81349-milc3098/28 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A059a0