NSN 5955-00-232-7055

Quartz Crystal Unit - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5955-00-232-7055

| Overall Length: |
|---|
| Between 1.907 inches and 1.937 inches |
| Terminal Length: |
| Between 0.625 inches and 0.655 inches |
| Overall Width: |
| 1.170 inches |
| Body Length: |
| 1.282 inches |
| Overall Thickness: |
| 0.411 inches |
| Terminal Diameter: |
| Between 0.123 inches and 0.127 inches |
| Mode Of Oscillation: |
| Fundamental |
| Circuit Resonance: |
| Antiresonance |
| Load Capacitance In Picofarads: |
| Between 34.5 and 35.5 |
| Specified Frequency: |
| 5.820 megahertz |
| Holder Cover Material: |
| Plastic |
| Operating Tempurature Range: |
| -55.0/+90.0 degrees celsius |
| End Application: |
| 6625-00-229-1049 |
| Center To Center Distance Between Terminals: |
| 0.490 mils and 0.510 centimeters |
| Drive Level Rating: |
| Between 27.0 milliwatts and 33.0 milliwatts |
| Frequency Tolerance For Operating Tempurature In Percent: |
| -0.005/+0.005 |
| Equivalent Resistance Value In Ohms: |
| 60.0 |
| Style Designator: |
| Rectangular body, pin terminals |
| Test Data Document: |
| 81349-mil-c-16 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |

excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental

and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-c-16 government specification

Shelf Life:

N/a

NSN 5955-00-232-7055

Quartz Crystal Unit - Page 2 of 2



| | ι | Jn | it | Of | Measure: |
|--|---|----|----|----|----------|
|--|---|----|----|----|----------|

--

Demilitarization:

No

Fiig:

A059a0

Mil-std (military Standard):

Mil-c-16 spec.